

## CONFIGURATION SHEET

Everything you need to consider when setting up your GARDiS Controller

### The benefits of a Web Embedded Controller



5000  
Users



1000+  
Access Groups



15,000  
Event Buffers




Up to 10  
wireless locks



Up to 10  
Slaves = 44 Doors

### How many doors?










### Select master unit



GARDiS  
2 Door  
5002-6002



GARDiS  
4 Door  
5002-6004

## Add an extension



GARDiS  
4 EXT  
5002-6005



GARDiS  
I/O Ext  
5002-6006




Aperio  
AH30 1-8  
Comms Hub  
2920-0555



Simons Voss  
Smart Intego  
Gateway Node  
2920-0556

## Choose your technology



Proximity



MIFARE

Sector

CSN



DESfire  
TDSi

## Choose your reader



GARDiS Mullion Reader  
5002-0600 - Proximity  
5002-0610 - MIFARE CSN  
5002-0620 - MIFARE Sector  
5002-0630 - DESfire



GARDiS Square Reader  
5002-0602 - Proximity  
5002-0612 - MIFARE CSN  
5002-0622 - MIFARE Sector  
5002-0632 - DESfire


## Credentials



Proximity  
4262-0245 - Card w/ logo + ID  
4262-0246 - Fobs



MIFARE  
2920-3002 - 1K CSN Card  
2920-3004 - 1K Sector Card  
2920-6020 - 4K DESfire Card


Note: A maximum of 10 extension units **or** 10 Wireless locks may be used.

Note: 44 doors available only when NO wireless or IO Expanders used.

TDSi Australia, Unit 6, 15-17 Chaplin Drive, Lane Cove West, NSW 2065

[WWW.TDSi.COM.AU](http://WWW.TDSi.COM.AU)

(02) 9906 4455

[sales@tdsi.com.au](mailto:sales@tdsi.com.au)

**COMVISION**  
visiotech | TDSi AUSTRALIA